



P2.66mm Crystal Series Technical Specification

P2.66mm Technical Specification	
Item	Technical Parameter
Pixel Pitch(mm)	2.66 mm
Pixel Density (dots/m ²)	147,456Pixel/m ² 36,864Pixel/Panel
LED Type	SMD 3 in 1 black LED
Module size(mm)	250x250mm
Module resolution	96x96
Cabinet Size (mm)	500x500x80 mm
Cabinet resolution	192x192
Cabinet Weight (kg)	11 kg
Driving Method (s)	1/16 s
Brightness (cd/m ²)	1,000 cd/m ² adjustable by software

STORMLED

Refresh Frequency(Hz)	≥ 3000 Hz adjustable by software
MTBF (H)	>10000 H
Max. Power Consumption(w/m ²)	150 w/m ²
View Angle	140°horizontally, 140°vertically
Grey Scale (color)	280 trillion
Color Temperature	R.G.B brightness 256 level adjustable, color temperature is adjustable according to requirements
IP(Protection Index) level	IP 43
Defects Rate	< 1/10000 dots
Life Span (H)	> 100000 H
Operating Voltage	AC220V $\pm 10\%$ /AC110V $\pm 10\%$ (Power can't be switched directly)
Operating Temperature	-20°C ~ +50°C
Operating Humidity	10%RH~90%RH
Certificates	CE,EMCclassA(TUV) ETL,RoHS